



#### KEY FEATURES

- > Suited for public environments
- > Cost efficient
- > Compact solution



## MULTIQ 219 Touch Signage Monitor 9/E07

P-LINE

### **COST EFFICIENT MONITOR FOR KIOSKS**

Digital Signage and web kiosks make it possible to engage with audiences in public spaces like never before. Involving constantly changing, interactive, and locally adapted displays makes your communication with customers both exciting and dynamic. It also gives you a practical and resource-efficient way of spreading your messages to broad audiences and measuring the effect.

The MultiQ Touch Signage Monitor 9 is designed for cost-efficient interactive touch and web-kiosk applications. Everything needed is built into the monitor and all you have to do to set it up is connect it to power and a network.

### **A NEW GENERATION**

The combination of MultiQ Touch Signage monitors and the Digital Signage Management System represents a new generation of digital signage solutions. It supports all the traditional digital signage functions, such as high MPEG 2/4 quality video, media scheduling and local storage for instant media access and minimized use of bandwidth.

On top of this, the solution embraces tools and technologies that are well known and used for Internet web applications – thereby enhancing capabilities way beyond those of traditional digital signage. Employing web standards such as HTML-5, JavaScript, Ajax the new generation of MultiQ Media players facilitates content and application creation, all using standard web development tools.

### **MADE FOR USE 24/7**

MultiQ Touch Signage Monitor 9 is designed for 24/7 operation and is suitable for retail environment with its metal housing and touch glass. The monitor has a flexible platform with unique possibilities for customization; optional chassis color, logo in print or relief, card reader, speakers etc.

# MULTIQ 219 Touch Signage Monitor 9/E07

## Technical specifications

P-LINE

201611/ENG/R1A

### DISPLAY

Panel Type	19", LCD TFT
Backlight type	LED
Resolution	1280x1024 (max)
Brightness	350 cd/m <sup>2</sup> (Typ.)
Contrast ratio	1500:1 (typ.)
Viewing angle	85° (H) x 85° (V) (CR 10:1, Typ.)
Number of colors	16.7 Mill (RGB 8-bit)
Response time	35 ms (Tye, on/off.)
Lamp life/MTBF	70.000 h (min)

### POWER

AC/DC adapter	Input: AC 100~240 V, 50~60Hz Output: +12 V DC, 5 A
Power consumption	45-46 W (Typ.), 50W (max excl. USB devices), 55W (max incl. USB load), 6 W soft shut down
Power management	VESA DPMS Compatible

### DIMENSIONS

With VESA	428 (W) x 358 (H) x 59 (D) mm
-----------	-------------------------------

### WEIGHT (NET)

With VESA	7,25 kg
-----------	---------

### ENVIRONMENT

Operating temperature	0 - 40°C
Operation Humidity	10 - 90%

### GENERAL

Incl accessories	AC/DC adapter - 1,5 m (black), Power cord - 1,8 m (black)
Regulations	Safety: CE
Warranty	3 years SendIT
Security	Kensington locking capability, Table locking (with stand)

### OPTIONS

Touch	Projective capacitive, 2 point Multi.touch
MSR	MagTek 3 tracks, USB HID, USB-KeyB Em., Serial
Built-in-speakers	2x2.0 W

### INTEGRATED MEDIA PLAYER

Operating System	Embedded Linux or embedded Windows (license fee apply) adapted for MultiQ Digital Signage
Processor	Intel® Celeron J1900
Storage	32 GB SSD
System memory	RAM 2 GB DDR
Connectivity	2xUSB 3.0, Ethernet RJ45, 3.5 mm audio out
Mounting	VESA (75 x 75) stand

### ACCESSORIES

Stands/brackets	POS-Pole, Wall bracket kit
-----------------	----------------------------



RoHS Compliant 2002/95/EG

©2016 MultiQ are registered trademarks or trademark applications of MultiQ International AB in various jurisdictions. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to change the specifications without prior notice.